#### TC-01TK VALVE

## 1PC REDUCED PORT 1000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE 1/4"-2"



1pc design considered most economical non-repairable valve


## TC-01B (FS) VALVE 1PC REDUCED PORT 2000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE ½"-2"





1 piece API 607 Fire Safe with ABS Type Approval.

## TC-02X VALVE 2PC FULL PORT 1000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE ½"-4"



2 piece design. Most economical Full Port Ball Valve

## TC-02XWS VALVE 2PC FULL PORT 1000 psi (WOG) water, oil, gas SEAL WELDED BALL VALVE, THREADED SIZE ½"-4"



2pc design economical valve with welded seal construction

## TC-0612M, TC-0612MC VALVE 2PC STANDARD PORT 2000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE $\frac{1}{4}$ "-1 2000 psi $1-\frac{1}{4}-3$ " 1500 psi



2 pce design with ISO 5211 mounting pad.

**Stainless and Carbon Steel in stock** 

#### *TC-0712M/TC-0712MC VALVE*

2PC STANDARD PORT ¼"-1" 2000 psi / 1 ¼"-3" 1500 psi (WOG) water, oil, gas BALL VALVE SIZE 250 WSP, CGT POLYMERS



2 pc Standard port 250 WSP (WORKING STEAM PRESSURE) ball valve w/ISO mounting pad

#### *TC-2000 VALVE*

2PC FULL PORT ¼"-1" 2000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE 1-1/4" -2" offered as TC-2000WS (Weld Seal)



2 pce economical full port design

#### TC-2000WS VALVE

2PC FULL PORT 2000 psi (WOG) water, oil, gas SEAL WELDED BALL VALVE, THREADED SIZE 1/4" - 2"



2pc valve full port design with weld seal body for OSHA applications

#### *TC-9000 VALVE*

2PC FULL PORT 1000 psi (WOG) water, oil, gas BALL VALVE, THREADED SIZE ½"-2"

(with ISO 5211 direct mount pad)



2 pce full port ball valve with ISO 5211 Direct Mount

For economical actuation applications

### TC-03T/B/S VALVE 3PC FULL PORT 1000 psi (WOG) water, oil, gas BALL VALVE SIZE ¼"-4"



3pc valve with swing-out design for easy installation and in line valve seat/seal replacement

## TC-03K, TC-03KC VALVE 3PC FULL PORT 1000 psi (WOG) water, oil, gas BALL VALVE,T/B/S SIZE ½"-2"



**3pc Contractor Compact valve with swing-out design for easy installation and in line valve seat/seal replacement** 

#### TC-3000T/B/S VALVE

3PC FULL PORT 1000 psi (WOG) water, oil, gas BALL VALVE, T/B/S SIZE ½"-4"

(with ISO 5211 direct mount pad)



3pc Direct Mount valve with swing-out design for easy installation and in line valve seat/seal replacement

### TC-3000TC T-CLAMP & TUBE ENDS END VALVE

3PC 1000 psi TRUE PORT TUBE END SANITARY BALL VALVE SIZE ½"-4" (with ISO 5211 direct mount pad )





**3pc valve Sanitary ball valve for Food Grade applications** 

**Full ISO 5211 Direct Mount** 

**Tri-Clamp and Tube O.D. ends** 

#### TC-4000 (FS), TC-4100 (FS) VALVE

3PC FULL PORT BALL VALVE, T/S SIZE ½"-1" 2000 psi 1-1/4 - 2" 1500 psi (WITH ISO 5211 DIRECT MOUNT PAD )





3pc valve Direct Mount ball valve
ABS Type Approved/USCG POSITIVE SHUT-OFF

### *TC-6000 (FS), TC-6100 (FS) VALVE*1PC 150# REDUCED PORT BALL VALVE, FLANGED SIZE ½"-6"



**API-607 Fire Safe Certified Unibody Design**Stainless and Carbon Steel in stock

#### TC-0802A VALVE

## 2PC 150# & 300# FULL PORT FLANGED BALL VALVE SIZE ½"-12"



2 PCE FULL PORT FLANGED END BALL VALVE
150# & 300# AVAILABLE

### TC-0802A VALVE 2PC 150# & 300# FULL PORT BALL VALVE, FLANGED SIZE 8"-12" WITH GEAR OP.



MANUAL GEAR OPERATOR STANDARD ON 10", 12"

AVAILABLE AS OPTION ON 8"

### *TC-5000 (FS), TC-5100* (FS) VALVE 2PC 150# FULL PORT BALL VALVE, FLANGED SIZE ½"-8"





API 607 Fire Safe valves with ABS Type Approval. USGC Positive Shut-Off Certified. Stainless and Carbon Steel in Stock.

8" STANDARD WITH MANUAL GEAR OPERATOR

### TC-5300 (FS), TC-5400 (FS) VALVE 2PC 300# FULL PORT BALL VALVE, FLANGED SIZE ½"-8"





API 607 Fire Safe valves with ABS Type Approval. USGC Positive Shut-Off Certified. Stainless and Carbon Steel in Stock.

8" STANDARD WITH MANUAL GEAR OPERATOR

# TC-7000 (FS) VALVE 2PC 150# FULL PORT BALL VALVE, FLANGED SIZE RANGE 1"-4" (with ISO 5211 direct mount pad)



**API-607 Fire Safe Certified & Direct Mount for economical actuation** 

#### TC-WL, TC-WT VALVE

#### 3 WAY REDUCED PORT 1000 PSI (WOG) WATER,OIL, GAS BALL VALVE, THREADED "L" PORT, "T" PORT SIZE ¼"-2"



FIELD ADJUSTABLE FLOW PATTERNS

TC-WLT-DM, TC-WTT-DM VALVE

3 WAY REDUCED PORT 1000 WOG BALL VALVE,

(with ISO 5211 direct mount pad)

THREADED "L" PORT, "T" PORT ¼" – 2"



# TC-WLF, TC-WTF VALVE 150# MULTI-PORT FLANGED 3 WAY BALL VALVE L-PORT, T-PORT, SIZE 2"- 6"



### 800 psi (WOG) water, oil, gas

TC-YS VALVE

Y STRAINER, THREADED, SOCKET-WELD SIZE ¼"-3"



# TC-YSF VALVE 150# R.F. FLANGED Y STRAINERS STAINLESS STEEL SIZE 2"-6"



TC-GT
200 PSI (WOG) WATER, OIL, GAS GATE VALVE, THREADED
SIZE 1/4-"-2"



## TC-GB VALVE 200 PSI (WOG) WATER, OIL, GAS GLOBE VALVE, THREADED SIZE 1/4-"-2"



# TC-GTF-ANSI VALVE 150 # LB & 300 # FLANGE END GATE VALVE ½" – 12" SIZE RANGE



# TC-GBF-ANSI VALVE 150 LB FLANGE END GLOBE VALVE SIZE ½"- 10"



## TC-CK, TC-CKS VALVE 200 WOG SWING CHECK VALVE THREADED & SOCKET WELD SIZE 1/4"-3"



## TC-CKF-ANSI VALVE 150 # & 300 # FLANGE END SWING CHECK VALVE

SIZE ½" - 12"



# TC-NDL VALVE 6000 PSI STAINLESS STEEL NEEDLE VALVES SIZE 1/8"- 1"



### SPECIAL HANDLES EXTENDED HANDLE FOR INSULATION

- Applicable Models:
- •TC-02T / TC-02TM / TC-02X

•TC-0612M / TC-0712M / TC-2000



•TC-03T/B/S / TC-03K

### SPECIAL HANDLES LOCKING OVAL HANDLE

- Applicable Products:
- •TC-02T / TC-02TM / TC-02X /
- •TC-0612M / TC-0712M
- TC-2000
- •TC-03T/B/S / TC-03K



FOR OSHA APPLICATIONS

## WWW.tachen.com click on Catalog section

- Click on Valves & Strainers to review all TCI valve products.
- •Click on TECHNICAL DATA / VALVE TORQUE DATA
- Certs click on CERTIFICATE
- •Click on valve P/N for **DESIGN FEATURES**:
- MATERIALS LIST:
- •PRESSURE TEMPERATURE RATINGS:
- **•DIMENSIONS:**

TCI would like to thank you for your time to review all of our valve products.

We look forward to working with all of you.

# The End Thank You